

Thales MissionLINK[®] on Iridium CertusSM

Dependable and
robust satcoms,
covering every
continent.



Thales MissionLINK®

Critical global coverage regardless of landscape or location.

- Certus 700 services (352kbps up/704kbps down & 256 kbps streaming capable)
- 100% global satellite coverage and low latency for critical data and voice communications
- Satellite to Land Mobile Radio extendable network through a unique Radio Gateway
- Easily integrates terrestrial cellular with built-in preferred routing switch



TERMINAL SPECIFICATIONS	
SIZE	12 in x 9 in x 2.3 in (30.5 cm x 22.9 cm x 5.8 cm)
WEIGHT	7.5 lb (3.4 kg)
POWER OPTIONS	Option 1: 10-32VDC Option 2: AC/DC supply with 12VDC *65W nominal/120W max
IP RATING	IP31
CONNECTORS	Front: RJ-45 LAN (3) Class 2 PoE RJ-45 WAN (1) for cellular, VSAT and other IP connections, RJ-14 POTS (2 independent phone lines) Rear: DC Power Input (10-32V) MIL-STD-1275D, DC Power Input (+12V Regulated), GPIO (RS-232, +12V out, Emergency, Radio Gateway, Discrete I/O), TNC - RF connection to Antenna, Wi-Fi - Reverse SMA, SIM card slot
MECHANICAL VIBRATION AND SHOCK	MIL-STD-810G, Test Method 514.6, Procedure 1, Category 20, Annex D Mil-STD 810G, Test Method 516.6, Procedure IV

ANTENNA SPECIFICATIONS	
High-gain, electronic phased array antenna with no moving parts to enable the fastest upload and download speeds to cover any land communications need from safety services, tracking and location services, out-of-band management to operational reporting and data transfers.	
SIZE	14 in dia. x 4 in h (35.6 cm dia. x 10.2 cm h)
WEIGHT	6.2 lb (2.8 kg)
POWER	Directly powered by the terminal at 24 VDC
IP RATING	IP66
OPERATING TEMPERATURE	-60 to +55 degrees C
MECHANICAL VIBRATION AND SHOCK	MIL-STD-810G, Test Method 514.6, Procedure 1, Category 20, Annex D Mil-STD 810G, Test Method 516.6, Procedure IV

*Specifications are subject to change without notice



Toll Free: +1 (866) 645-5087
info@stellarsolutions.ca
www.stellarsolutions.ca



2081:013120:V5

Thales has a policy of continuous development and improvement and consequently the equipment may vary from the description and specification in this document. This document may not be considered as a contract specification. Graphics do not indicate use or endorsement of the featured equipment or service. Copyright © 2020 Thales